1/35 **Scale RAY HARRYHAUSEN CYCLOPS**



INSTRUCTIONS FOR ASSEMBLING

YCLOPS **PLASTIC MODEL KIT**

IMPORTANT - READ THIS FIRST!



PRO TIP!

You can use soft steel wool to smooth out the seam lines after gluing everything together. After the glue has dried, simply scrub gently over the seam lines a few times until they are no longer visible.



LET US KNOW **MORE IN THIS SURVEY**



https://forms.gle/HKDqnimZ4fkR6QpZ9

KEEP AN EYE OUT FOR THESE KITS!



OUniversal City Studios LLC and Amblin Entertainment, Inc. All Rights Reserved

•This model needs to be assembled. Read the instructions thoroughly before constructing the model.

• After taking the product out of the plastic bag, tear the plastic bag and discard it safely, since there will be a danger of suffocation if young children mishandle it. • Cleanly clip the parts from the trees, discarding them after all the parts have been removed.

• Due to manufacturing circumstances, it is unavoidable that there will be sharp points that may cause harm. Be sure not to play or mishandle the trees or use them for unintended purposes. Households with young children should be particularly careful.

• Use nippers for removing parts and finish any burrs remaining on the parts using a craft knife or file. Be cautious of mishandling nippers, craft knives or files as they may result in cuts to the hands or fingers. Children younger than 10 years of age should have the work carried out by a parent or guardian.

 As the kit contains small parts, please keep them out of reach of younger children as they may cause a choking hazard. Due to the danger of mistakenly swallowing parts, be absolutely certain to keep them away from unsupervised children younger than the target age.

• (In the situation where you use cement or paints, take care of the following points). If cement or paint gets in your eyes, immediately wash the affected area with large amounts of water and consult a doctor. Do not use cement or paint in enclosed rooms, since there will be danger of toxic inhalation. Absolutely do not use cement or paint near sources of open flame, as there will be danger of ignition.

• Do not leave the product in locations subject to direct sunlight or in places with high temperature or high humidity.

CONTACT US

ADDRESS: 9F, Hiranomachi Takahashi Bldg., Hiranomachi 1-8-8, Chuo Ward, Osaka City, Osaka, Japan 541-0046 EMAIL: info@ric-toy.com

We are availabe on non-holiday weekdays from 10:00 to 18:00 (JST)

2023 X PLUS CO., LTD. MADE IN CHINA



THE **MONSTER THAT**

IN THE DARK

Package Art by Antonio J. Manzar on of The Rav and Diana Harrvhausen F ed with the pern

FOR SUGGESTED DETAIL PAINTING **SCHEME - SEE ILLUSTRATIONS.** Paint parts as indicated and allow to dry before assembling.

NOTE! PLEASE TEST FIT PARTS BEFORE GLUING TO ENSURE PROPER FIT.

NOTE - Do not glue leg parts 30#, 31# together before Step 6.

Step 1 - Glue lower teeth part #18 into lower mouth #17, then upper teeth part #21 into upper mouth #20. Tongue part #19 is now attached to the lower mouth section. It may be best to paint these parts at this time. Attach upper and lower mouth halves together.

Step 2 - Take head half #13 and slip in horn #12, eye/nose #16, then the assembled mouth from step 1. Carefully assemble head half #14 to head half #13, clamping in parts #12, #16, and assembled mouth. Add ears #15 (right ear) and #22 (left ear). Set assembled head aside.

Step 3 - Assemble body halves #1 and #2.

Step 4 - Assemble right leg parts #28 and #29.

Step 5 - Slide rear left leg part #31 into front pelvic section #23. Attach assembled torso halves into front pelvic section. Attach front left leg part #30 to rear leg that is in the pelvis. Slide right assembled leg into place in the pelvis. Clamp upper body and legs into pelvis with rear pelvic section #24.

Step 6 - Attach right arm parts #3 and #4, then insert fingers #5, #6, #7 on the assembled right arm. Attach left arm parts #8 and #9, next insert fingers #10 and #11 on the assembled left arm.

Step 7 - The arms and head can be inserted at this time. The figure is now complete.

Step 8 - Attach #35 latch to #34 upper door.

Step 9 - #33B latch brace can be glued to roof section #37. Glue axle #36 to the bottom of roof section #37.

Step 10 - Carefully clip both #40 rings into the holes in upper door #34.

Step 11 - Assemble cage wall #32 to front wall #38. Carefully slide the assembled door #34 onto the #36 axle through the #40 rings. The roof can be attached to the assembled cage walls #32 and #38.





Left Cage Wall

Front Cage Wall (#38)

Name Plate (#51) CYCLOPS (#50)

IF YOU ARE INDEED A PAINTER, WHY NOT USE YOUR GREAT SKILLS TO PAINT THE ONE-EYED MONSTER?

Step 12 - Now attach cage floor #33.

Step 13 - Assemble the prisoner by clamping arm section #43 between body halves #41 and #42. Turban #44 can be glued on now. The prisoner is now ready to be placed in the cage. Now attach cage wall #39 to assembled cage.

Step 14 - Assemble skeleton body halves #46 and #49, then attach right arm #45 and left arm #48. Skull #47 is last and it can be glued in place at the back of the caae.

Step 15 - Assemble club halves #25 and #26. Be sure all holes are open (use drill to open them), then insert the seven #27 spikes into the club.

Step 16 - Name plate #51 can be placed on base #50.

Step 17 - Place finished Cyclops, the assembled cage, and the assembled club onto the base for the finishing touches.



Assembled Club